

# ELE-1073-ITS, LCD Display, 12.1" For 32MP Pendant

**Note: This kit replaces the 14" Monochrome VGA Display in 32MP Pendants**

1. Unplug the AC Power and VGA Cable from the old Monitor. Remove the old monitor, the mounting tray and the plastic bezel from the front.
2. Attach the new Metal Bezel on the front of the Pendant using the 4 screws and nuts provided and tighten them down.
3. From the back mount the new LCD Screen using the 4 screws and nuts provided. Adjust the display so all 4 screws are straight and then tighten them down.
4. Plug the 4 pin AC Power plug in and the VGA Cable. You are ready to power up.



## Adjustments for Contrast, Brightness, Horizontal and Vertical Position

1. On the Remote press Menu, Down Arrow then Left or Right Arrow to Adjust Contrast.
2. Press Down Arrow again and Left or right Arrow to Adjust Brightness.
3. Press Menu again and Right Arrow 3 times, then Down Arrow and Left or Right Arrow to Adjust Vertical Position.
4. Press Down Arrow again and Left or Right Arrow to Adjust Horizontal Position. Press Menu again to exit.

**If you have any questions call tech support at 1-818-727-1887**

**or visit us at [www.itscnc.com](http://www.itscnc.com)**